

UniFi[®] SWITCH



UniFi Switch Lite 8 PoE

The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3af PoE+ that provide up to a total PoE wattage of 52W for UniFi Access Points or other PoE devices. Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.



Mechanical

Dimensions	99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25")
Weight	450 g (15.87 oz)

Hardware

Total Non-Blocking Line Rate	8 Gbps
Max. Power Consumption	8W
Power Method	54VDC, 1.1A Power Adapter
Power Supply	External 54V/60W Power Adapter
Supported Voltage Range	DC 50V to 57V
Networking Interfaces	(8) 10/100/1000 Mbps Ethernet RJ45 Ports
PoE Interfaces	(4) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-)
Management Interface	Ethernet In-Band
Max. PoE+ Wattage per Port by PSE	30W
Modes	SMB Layer 2 PoE Gigabit Ethernet Switch
Operating Temperature	-15 to 40° C (5 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	CE, FCC, IC

LEDs

System	(1) Power, Blue/White Flashing White: Bootup in Progress Flashing Blue: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
Ethernet	Green: 1G, Amber: 10/100 Mbps
PoE	Amber: IEEE 802.3af/at

