

NetworX Solution 2000 Series




Microprocessor based 3x3 technology

Specifications

Technology	3x3 Technology (Patented)
Input Voltage	10-14V AC/DC
Current	Alarm Condition: 24mA Standby, w/o status LED: 32mA Standby, w/status LED: 36mA Standby, w/latched alarm and status LED: 38mA
Low Voltage Detect	6.40 Volt (400mV Hysteresis)
Relay Contacts	100V DC, 10VA, 500mA
Sensitivity	Automatically adjusted
Case Materials	Flame retardant injection Molded ABS
Operating Temperature	32°F to 120°F (0°C to 49°C)
Maximum Coverage:	
NX-2000	25'
NX-2100	20'
NX-2200	20'
Color	White

NetworX Technical Support: 800-727-2339

Dimensions



Ordering Information

Model	Description
Solution 2000	Maximum detection range of 25', surface mount, visible LED
Solution 2100	Maximum detection range of 20', surface mount, visible LED
Solution 2200	Maximum detection range of 20', surface mount, visible LED



www.gesecurity.com

1275 Red Fox Road
Arden Hills, MN 55112
Phone: 651-777-2690
USA & Canada: 800-777-5484
Technical Service: 800-777-2624

12345 SW Leveton Drive
Tualatin, OR 97062
Phone: 503-692-4052
USA & Canada: 800-547-2556
Technical Service: 800-727-2339
Faxback: 800-483-2495



www.gesecurity.com

NetworX Solution 2000 Series

Microprocessor based 3x3 technology

Overview

The NetworX Solution 2000 Series glassbreak sensors are the most advanced in glassbreak detection the security industry has ever seen. The Solution 2000 Series uses patented microprocessor based 3x3 technology. With 3x3 technology, these new detectors identify and qualify multiple groups of data from three specific frequency ranges to determine whether any of the sounds present match the signature of breaking glass.

With a maximum detection range of 20-25 feet, a low-profile design and the option of surface or flush mount, these detectors are great for either residential or commercial applications.

With the NetworX Solution 2000 Series, you can rest assured that you have the most reliable glassbreak detectors in the world.



Standard Features

- 3x3 technology
- Microprocessor based
- Automatic adjustment
- Detects all glass types
- Power/Status LED
- Alarm memory LED
- Push button test mode
- Ceiling or wall mount
- UL listed