

Access Point U6+



Mechanical

Dimensions	Ø160 x 33 mm (Ø6.3 x 1.3")
Weight	Without mount: 338 g (0.75 lb) With mount: 413 g (0.91 lb)
Enclosure materials	Top cover: polycarbonate Bottom cover: aluminum
Mount materials	ABS, SGCC steel

Hardware

Networking interface	(1) GbE RJ45 port	
Management interface	Ethernet	
Power method	PoE	
Supported voltage range	44–57V DC	
Max. power consumption	9W	
Max. TX power	2.4 GHz	23 dBm
	5 GHz	23 dBm
MIMO	2.4 GHz	2 x 2
	5 GHz	2 x 2
Throughput rate	2.4 GHz	573.5 Mbps
	5 GHz	2402 Mbps
Antenna gain	2.4 GHz	3 dBi
	5 GHz	5.4 dBi
LED	White/blue	
Button	Factory reset	
Mounting	Wall/ceiling (included)	
Operating temperature	-30 to 60° C (-22 to 140° F)	
Operating humidity	5 to 95% noncondensing	
Certifications	CE, FCC, IC	

Software

WiFi standards	802.11a/b/g WiFi 4/WiFi 5/WiFi 6
Wireless security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)
BSSID	8 per radio
VLAN	802.1Q
Advanced QoS	Per-user rate limiting
Guest traffic isolation	Supported
Zero wait DFS	Not supported
Concurrent clients	300+

